

Crystal Coat SB

Concrete/Paver Sealer

130

USE:

Crystal Coat SB (Solvent-Based) Sealer is designed to protect and beautify interlocking brick pavers, *Texture-Krete 2000* and all other properly prepared concrete surfaces, interior or exterior.

DESCRIPTION:

Crystal Coat SB is formulated from 100% acrylic resins. *Crystal Coat SB* is higher in solid content than most conventional concrete sealers and is V.O.C. compliant. *Crystal Coat SB* provides water and UV light resistance with excellent adhesion to a variety of substrates.

FEATURES & BENEFITS:

- NON-YELLOWING: Enhances true substrate color
- DURABLE: Weather, Salt & UV Light resistant
- CHEMICAL RESISTANT: Retains gloss & appearance
- EASY TO CLEAN: Resists staining & tire marks
- FAST DRYING: Saves time

INSTRUCTIONS FOR USE:

Surface Preparation: New concrete should cure at least 28 days. Surfaces must be clean and dry before sealing. All dirt, grease, oil, wax, and potential contaminants must be removed. For best results, use **ICT Total Klean**, all purpose cleaner and degreaser, and pressure wash.

Application: Apply sealer with a brush, roller, or spray. Do not brush or roll excessively. Avoid runs or sags. Two thin coats (2 dry mills) provide the best results. Do not apply *Crystal Coat SB* Sealer more frequently than every 18 months to avoid build up of the sealer.

Note: Coated surfaces may become slippery when wet. ICT Diamond Dust should be incorporated in this situation. It is the sole responsibility of the applicator to determine whether a non-skid additive should be used.

LIMITATIONS:

Apply when materials, surface and air temperatures are above 55°F. Do not apply when dew point is within 5°F of air temperature. Do not apply in damp or threatening weather. (Low temperatures and high humidity will affect drying and curing times.) Do not dilute. Store above 40°F. Do not apply when temperature of the surface to be coated is below 55°F, or when temperatures are expected to fall below this point within 4-8 hours of initial cure.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES. DO NOT BREATHE VAPORS. DO NOT TAKE INTERNALLY. DO NOT STORE IN DIRECT SUNLIGHT. KEEP AWAY FROM HEAT AND OPEN FLAME. USE WITH ADEQUATE VENTILATION. CONTAINS XYLENE.

CHARACTERISTICS AND TECHNICAL DATA

<u>Liquid Properties</u>	<u>Test Results</u>
Weight/Gallon (± 1)	8.0 lbs./gal.
% Solids (± 1)	33%
Gloss @ 60°F.....	95
Appearance Wet.....	Clear
Appearance Dry.....	Clear
Coverage/Gallon.....	Up to 300 sq. ft. per gal.
Clean Up.....	Xylene, Lacquer thinner
Sheen.....	Full gloss 2-3 coats
Dry to touch.....	30 min.
Dry to Recoat.....	4 hours
Cured...	48-72 hours
Shelf Life.....	1 yr min. (closed container)
V.O.C.....	less than 600 grams/liter
Liters/gallon.....	3.875 liters

**** CONTAINS XYLENE ****

ICT Corporation

2410 McJunkin Road * Lakeland, FL 33803
 (Nationwide): 888-296-5236 * (Local): 863-665-8787 *(Fax): 863-666-2768
 (Email): info@innovativeconcrete.com
 www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 12-18 months from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.