

Ure-Seal H₂O

2-Part Urethane Clear Coat

150-KIT

USE:

ICT Ure-Seal H₂O is a 2-part water reducible crystal clear Urethane. It is a high performance clear coating that can be used inside or out to protect and enhance any properly prepared floor for years of service. **Ure-Seal H₂O** cleans up with soap and water and is as easy to apply as it is to clean up afterwards.

DESCRIPTION:

ICT Ure-Seal H₂O has excellent abrasion and chemical resistance with a high gloss finish. The mild odor makes it ideal for interior applications. **Ure-Seal H₂O** will not yellow and will form a very hard protective coating for high traffic area, counter tops, restaurants, decorative concrete, brick pavers. **Ure-Seal H₂O** can be used over epoxy flooring, garage floors, anywhere that high durability and superior chemical resistance is required.

APPLICATION:

ICT Ure-Seal H₂O is a two component product. Mix using a low speed drill or jiffy mixer for 1-2 minutes. Do not whip air into the mixture. Apply with a short nap roller or a brush. If spray equipment is used, thoroughly clean after use. Once material cures, you will not be able to remove it from the spray apparatus. Do not apply to thick or bubbles will form. If a second coat is required, it must be applied after the initial coat is dry to touch but before it cures completely. It must be applied no less than 6 hours and no more than 15 hours after the initial coat is applied. Application viscosity can be adjusted by adding small amounts of water after component I and component II are mixed. Solids will be decreased when additional water is added. This will also reduce the gloss.

CHARACTERISTICS AND TECHNICAL DATA

Weight/Gallon.....	8.98 lbs./gal.
% Solids ± 1	48%
Gloss @ 60° Specular....	87
Dry Time (77°F,50% RH)	6 hrs.
Dry to Recoat.....	6 hrs. min/15 hrs. max
Return to Service	24-48 hrs.
Appearance Wet.....	Milky White
Appearance Dry.....	Clear
Coverage/Gallon.....	225 sq. ft / gal @ 3 mils
Maximum DFT:	6 mils
Pot Life after mixing	3 hrs. @ 77°F
Shelf Life.....	Six months @ 77°F
V.O.C	less than 50 grams/liter

FEATURES AND BENEFITS:

- Non-yellowing
- Excellent Chemical Resistance
- Low VOC
- Interior or Exterior Use
- High Performance
- Excellent UV Resistance
- Low Odor
- High Gloss
- Easy Clean-Up

LIMITATIONS:

Must be stored in air tight container to prevent evaporation and contamination with foreign material. All surfaces must be moisture free prior to application. Do not apply when surface and air temperatures are below 55°F or when dew point is within 5°F of air temperature. Any mixed material if not used within 2 hours of mixing should be discarded, this time may be increased by keeping the material in a cool dry place. Do not freeze, store above 40°F. If re-coat time is exceeded surface must be lightly abraded prior to applying second coat.

PRECAUTIONS:

Keep out of reach of children. Applicator should wear protective eyewear and gloves. Do not take internally. Do not store in direct sunlight or excessive heat. Keep from freezing. Refer to the MSDS for this product for safety recommendations related to working with this product. Do not allow this product to freeze. Do not apply below 50°F.

PACKAGING:

Available in 1 and 5 gallon kits.

ICT Corporation

2410 McJunkin Road * Lakeland, FL 33803
(Nationwide): 888-296-5236 * (Local): 863-665-8787 *(Fax): 863-666-2768
(Email): info@innovativeconcrete.com
www.innovativeconcrete.com